

Steam / Hot / Cold Water: Diesel Heated, Electric Motor

The **HP Series** combines the cleaning power of high pressure and high water flow with the grease cutting effectiveness of hot water. Simply pull the trigger on the spray gun, and instantly the machine turns itself on and delivers high pressure cleaning power. The temperature can be adjusted to cold, hot, or steam for any cleaning application. The portable design and stainless steel construction offers years of trouble free service and cleaning performance anywhere electrical power is available.

PRESSURE	3000psi
FLOW CAPACITY	3.9gpm
OUTLET TEMP	Adjustable up to 250°F (150°F rise)
POWER / ENGINE	8.0 hp
VOLTS/PHASE/AMPS	Dual rated for 208v or 230v - 1ph, 37amp
CONTROLS/SWITCHES	Lighted on/off and lighted burner switch, thermostat, hour meter
PUMP	Cat Pump, Oil Bath, Triplex Ceramic Plunger, Brass Head, Stainless Steel Valves
POWER DRIVE	V Belt drive
PRESSURE CONTROL	Adjustable pressure unloader and wand, safety relief valve, safety burst disc
WATER SUPPLY	3-1/2 gal. float tank
PRESSURE HOSE	3/8" x 50' 5800psi non-marking hose
SOAP INJECTION	Inlet chemical injection, injects at full pressure
GUN / WAND	48" molded insulator, adj. pressure wand with quick coupler
NOZZLE	#4.5 (15°, 40°) #4.0 (25° Steam)
BURNER COIL	Spiralast™ robotically fused 1/2" sch. 80 steel pipe, cold rolled 4 spiral, ceramic insulation
BURNER / POWER	Oil Fired, Forced Draft, Automatic Ignition, Fuel Solenoid, Fuel Filter with Water Separator
BURNER FUEL / CAP	Diesel fuel #1 or #2, Kerosene, Stove oil, JP8 fuel, 8 gallon capacity– 352,800 Btu input
CONSTRUCTION	All Stainless: frame, panels, coil wrap, and double wall coil end caps
WHEELS	4) 13" tires installed
NET WEIGHT / DIM	470#, 46"x29"x39"


* Specifications subject to change without notification and may vary due to ambient conditions

Featuring:

- ✓ **Performance:** High heating ability and high flow increases cleaning speed and power
- ✓ **Portability:** Compact design for versatility and maneuverability.
- ✓ **Durability:** All Stainless steel construction and panels for lifetime corrosion resistance
- ✓ **Efficient:** High output diesel burner system offers clean burning and continuous hot water.
- ✓ **Convenient:** E.T.S. Electronic Trigger Start, 60 second delay Auto Off avoids risk of pump overheating and expensive thermal damage. Also features adjustable pressure at the wand

Options...

Hose Reel (AR189), Wet Sandblaster, UL1776, CSA certification can be ordered with GFCI option (ACE00), Downstream injection kit



TO: _____
 COMMENTS: _____
 YOUR PRICE: _____
 DISTRIBUTED BY: _____