



Item # 216X4, Four Wheel Series Pressure Washer

Electric, Oil Fired, 4 Pneumatic wheels, Belt driven tri-plex pump, High-efficiency electric motor, Non-corrosive float tank, High-pressure detergent application, Trigger gun, Schedule 80 coil, 2.0 GPM/1600 PSI/ 2.3 HP



[Specifications](#) | [Manufacturing Notes](#)

Specifications	
Flow Rate	2.0 gpm
Pressure	1600 psi
Pump Style	Belt Drive Oil Bath Triplex
Motor Power	2.3 hp
Motor Voltage	115 V
Motor Fuse Rating	20 A
Shipping Weight	535 lb
Coil Type	Schedule 40
Coil Construction Type	Steel Pipe
Coil Length	126 ft
Burner Type	#1 Diesel Kerosene
Burner Pressure Atomizing Temperature	175000 Btu
Fuel Tank Construction Material	Plastic
Stack Size	8 in

Optional Parts/Features	Temperature Control
Chemical Features	Precise Metered
Float Tank Construction Material	Stainless Steel
Steam Capacity	60 gal/h
Length	46 in
Width	31 in
Height	49 in
Fuel Tank Capacity	8 gal
Fuel Consumption Capacity	1.25 gal/h
Number of Phase	1

Manufacturing Notes	
Manufacturing Notes	<ul style="list-style-type: none"> • All 115 volt units have ground fault interrupters standard. • For Capacity and Pressure: Gallonages and pressure may vary $\pm 5\%$ due to manufacturing tolerances in components. • Motor/Voltage: Special voltages on request. Gallonages and pressure may be less on 3 phase current. • Xtreme models same specifications plus Schedule 80 coils, Hi Limit Control, Fuel Solenoid and Stainless Steel Coil Wrappers (X4X models).

--