



**Item # 420X4, Four Wheel Series Pressure Washer**

Electric, Oil Fired, 4 Pneumatic wheels, Belt driven tri-plex pump, High-efficiency electric motor, Non-corrosive float tank, High-pressure detergent application, Trigger gun, Schedule 80 coil, 4.0 GPM/2000 PSI/ 5 HP



[Specifications](#) | [Manufacturing Notes](#)

Specifications	
<b>Flow Rate</b>	3.7 gpm
<b>Pressure</b>	2000 psi
<b>Pump Style</b>	Belt Drive Oil Bath Triplex
<b>Motor Power</b>	5 hp
<b>Motor Voltage</b>	230 V
<b>Motor Fuse Rating</b>	30 A
<b>Shipping Weight</b>	545 lb
<b>Coil Type</b>	Schedule 40
<b>Coil Construction Type</b>	Steel Pipe
<b>Coil Length</b>	126 ft

<b>Burner Type</b>	#1 Diesel Kerosene
<b>Burner Pressure Atomizing Temperature</b>	350000 Btu
<b>Fuel Tank Construction Material</b>	Plastic
<b>Stack Size</b>	8 in
<b>Optional Parts/Features</b>	Temperature Control
<b>Chemical Features</b>	Precise Metered
<b>Float Tank Construction Material</b>	Stainless Steel
<b>Steam Capacity</b>	120 gal/h
<b>Length</b>	46 in
<b>Width</b>	31 in
<b>Height</b>	39 in
<b>Fuel Tank Capacity</b>	8 gal
<b>Fuel Consumption Capacity</b>	2.5 gal/h
<b>Number of Phase</b>	1

Manufacturing Notes <span style="float: right;">—</span>	
<b>Manufacturing Notes</b>	<ul style="list-style-type: none"> <li>• For Capacity and Pressure: Gallonages and pressure may vary <math>\pm 5\%</math> due to manufacturing tolerances in components.</li> <li>• Motor/Voltage: Special voltages on request. Gallonages and pressure may be less on 3 phase current.</li> <li>• Xtreme models same specifications plus Schedule 80 coils, Hi Limit Control, Fuel Solenoid and Stainless Steel Coil Wrappers (X4X models).</li> </ul>

--