



**Item # 4231, Gas Fired Series Pressure Washer**

Stationary Gas-Fired Industrial Hot High Pressure Washer: Natural gas or LP fired; Belt-driven tri-plex pump; High-efficiency electric motor; non-corrosive float tank; High-pressure detergent application; Trigger gun; 3.7 GPM; 2300 PSI/ 6 HP; 230V 1 PH; 800 pounds



[Specifications](#) | [Manufacturing Notes](#)

Specifications	
<b>Flow Rate</b>	3.7 gpm
<b>Pressure</b>	2300 psi
<b>Pump Style</b>	Oil Bath Triplex
<b>Motor Power</b>	6 hp
<b>Motor Voltage</b>	230 V
<b>Number of Phase</b>	1
<b>Natural Gas Consumption</b>	305 ft <sup>3</sup> /h
<b>Liquid Petroleum Gas Consumption</b>	3.8 gal/h
<b>Coil Type</b>	Schedule 80
<b>Coil Construction Type</b>	Steel Pipe
<b>Coil Length</b>	243 ft

<b>Coil Inner Diameter</b>	5/8 in
<b>Natural Gas Aspirated Burner Temperature</b>	320000 Btu
<b>Stack Size</b>	12 in
<b>Standard Parts/Features</b>	Temperature Control
<b>Chemical Features</b>	Precise Metered
<b>Float Tank Construction Material</b>	Stainless Steel
<b>Float Tank Type</b>	Standard
<b>Steam Capacity</b>	120 gal/h
<b>Length</b>	55 in
<b>Width</b>	54 in
<b>Height</b>	25 1/2 in
<b>Shipping Weight</b>	815 lb

Manufacturing Notes <span style="float: right;">—</span>	
<b>Manufacturing Notes</b>	<ul style="list-style-type: none"> <li>• Also available as oil fired model.</li> <li>• Capacity and Pressure: Gallonage and pressure may vary ±5% due to manufacturing tolerances in components.</li> <li>• Motor: Special voltages on request. Gallonages and pressure may be less on 3 phase current.</li> <li>• Coil: ASTM steel pipe, spiral wound, cold water wrap design, removable wheel kits are all optional.</li> <li>• All models available ETL approved to UL1776 and CSA B140.11-M89 specifications.</li> </ul>

