Item # 430X4, Four Wheel Series Pressure Washer

Electric, Oil Fired, 4 Pneumatic wheels, Belt driven tri-plex pump, High-efficiency electric motor, Non-corrosive float tank, High-pressure detergent application, Trigger gun, Schedule 80 coil, 3.8 GPM/3000 PSI/8 HP



<u>Specifications</u> | <u>Manufacturing Notes</u>

Specifications	-
Flow Rate	3.8 gpm
Pressure	3000 psi
Pump Style	Belt Drive Oil Bath Triplex
Motor Power	8 hp
Motor Voltage	230 V
Motor Fuse Rating	40 A
Shipping Weight	715 lb
Coil Type	Schedule 80
Coil Construction Type	Steel Pipe
Coil Length	158 ft

	#1 Diesel
Burner Type	Kerosene
Burner Pressure Atomizing Temperature	385000 Btu
Fuel Tank Construction Material	Plastic
Stack Size	8 in
Optional Parts/Features	Temperature Control
Chemical Features	Precise Metered
Float Tank Construction Material	Stainless Steel
Steam Capacity	120 gal/h
Length	54 in
Width	32 in
Height	49 in
Fuel Tank Capacity	8 gal
Fuel Consumption Capacity	2.75 gal/h
Number of Phase	1
Manufacturing Notes	_
Manufacturing Notes	 For Capacity and Pressure: Gallonages and pressure may vary ±5% due to manufacturing tolerances in components. Motor/Voltage: Special voltages on request. Gallonages and pressure may be less on 3 phase current. Xtreme models same specifications plus Schedule 80 coils, Hi Limit Control, Fuel Solenoid and Stainless Steel Coil Wrappers (X4X models).