



Item # 5301, Gas Fired Series Pressure Washer

Stationary Gas-Fired Industrial Hot High Pressure Washer: Natural gas or LP fired; Belt-driven tri-plex pump; High-efficiency electric motor; non-corrosive float tank; High-pressure detergent application; Trigger gun; 5.0 GPM; 3000 PSI/ 10 HP; 230V 1 PH or 3 PH; 860 pounds



[Specifications](#) | [Manufacturing Notes](#)

Specifications	
Flow Rate	5 gpm
Pressure	3000 psi
Pump Style	Oil Bath Triplex
Motor Power	10 hp
Motor Voltage	230/460 V
Number of Phase	1 3
Natural Gas Consumption	420 ft ³ /h
Liquid Petroleum Gas Consumption	5.4 gal/h
Coil Type	Schedule 80
Coil Construction Type	Steel Pipe
Coil Length	243 ft

Coil Inner Diameter	1/2 in
Natural Gas Aspirated Burner Temperature	440000 Btu
Stack Size	12 in
Standard Parts/Features	Temperature Control
Chemical Features	Precise Metered
Float Tank Construction Material	Stainless Steel
Float Tank Type	Standard
Steam Capacity	150 gal/h
Length	55 in
Width	54 in
Height	25 1/2 in
Shipping Weight	885 lb

Manufacturing Notes	
Manufacturing Notes	<ul style="list-style-type: none"> • Also available as oil fired model. • Capacity and Pressure: Gallonage and pressure may vary ±5% due to manufacturing tolerances in components. • Motor: Special voltages on request. Gallonages and pressure may be less on 3 phase current. • Coil: ASTM steel pipe, spiral wound, cold water wrap design, removable wheel kits are all optional. • All models available ETL approved to UL1776 and CSA B140.11-M89 specifications.

