



Item # 5355J, Gas and Diesel Series Pressure Washer

Gas engine Drive; Oil-fired; Hot high pressure; Skid mount; Belt-driven tri-plex pump; Stainless steel wrapper and control panel; 12V burner; Electric start; Black; 126' Schedule 80 coil; 5.0 GPM/ 3500 PSI/ 20 HP Honda (electric) 765 pounds



[Specifications](#) | [Manufacturing Notes](#)

Specifications	
Flow Rate	5 gpm
Pressure	3500 psi
Pump Style	Ceramic Plungers Oil Bath Triplex
Engine Type	Honda Electric Start Belt Drive
Engine Power	20 hp
Coil Construction Type	Steel Pipe
Coil Type	Schedule 80
Coil Inner Diameter	1/2 in
Coil Length	126 ft
Burner Type	#1 Diesel Kerosene
Burner Pressure Atomizing Temperature	350000 Btu

Burner Auto Ignition Voltage	12 V
Fuel Consumption Capacity	2.5 gal/h
Fuel Tank Capacity	9.5 gal
Gas Tank Capacity	6 gal
Rising Temperature	110 °F
Chemical Features	Precise Metered
Float Tank Construction Material	Stainless Steel
Optional Parts/Features	Temperature Control
Length	48 in
Height	38 1/2 in
Width	34 in
Shipping Weight	875 lb

Manufacturing Notes	
Manufacturing Notes	<ul style="list-style-type: none"> ● For Capacity and Pressure: Gallonage and pressure may vary ±5% due to manufacturing tolerances in components. ● Engine: Batteries not included. ● Coil (Steel Pipe): ASTM A-53 steel pipe, spiral wound, cold water wrap design, removable. Wheel kits are optional. ● All 12 volt burner units available with optional high limit control. ● All models available ETL approved to UL1776 and CSA B140.11-M89 specifications. ● Specifications subject to change without notice.

