

### Cold (HOT\*) Water: Electric Powered – Stationary or Portable

The **CW Series** is a unique washer with hot water inlet capabilities that saves you time and money. Pressure clean thoroughly using your existing hot-water supply\* (up to 165°F standard or up to 190°F with available options). The CW's versatile design allows it to be wall-mounted, stationary or portable depending on the cleaning task or application. The adjustable pressure wand and auto start/time delay shutdown features give the operator total control from the wand – no traveling back and forth to the unit to adjust the pressure or turn switches. The heavy-duty industrial components, stainless steel frame/cover, and a low rpm belt drive pump for long lasting performance.

<b>PRESSURE</b>	3000 psi	
<b>FLOW CAPACITY</b>	4.8 gpm	
<b>POWER / ENGINE</b>	10 hp	
<b>VOLTS / PHASE / AMPS</b>	E3 is dual rated for 208v or 230v - 3ph, 29amp	E4 is 460v – 3ph
<b>CONTROLS / SWITCHES</b>	Hour meter, lighted on/off switch, soap control	
<b>PUMP</b>	General Pump, triplex ceramic plunger	
<b>POWER DRIVE</b>	V-Belt drive with EZ Align™ pump rail	
<b>PRESSURE CONTROL</b>	Adjustable pressure unloader, 24v adjustable timer with 7 to 300 second control	
<b>WATER SUPPLY</b>	Pressure feed from garden hose	
<b>WATER TEMPERATURE</b>	Inlet water temperature up to 165°F from hot water source, up to 190°F* with options	
<b>SOAP INJECTION</b>	Downstream soap injection included, inlet soap injection option available	
<b>PRESSURE HOSE</b>	3/8" x 50' 3000psi wire braided hose	
<b>GUN / WAND</b>	48" molded insulator, adj. pressure wand with quick coupler	
<b>NOZZLE</b>	#5.5 x 15°, 25°, 40°	
<b>FRAME CONSTRUCTION</b>	Stainless steel frame and removable cover	
<b>WHEELS</b>	Optional wheel / handle kit	
<b>DIMENSIONS (LxWxH)</b>	29" x 21" x 15" (31" x 31" x 20" with wheels, plus handle height)	
<b>NET WEIGHT</b>	190#	

Specifications subject to change without notification and may vary due to ambient conditions.

\* CW Series accepts water from hot water heater or other hot water source up to 165°F as equipped, or up to 190°F with an optional seal or pump upgrade



#### Featuring:

- ✓ **All Stainless Construction** is corrosion resistant and sanitary, ideal for use in food processing or medical facilities
- ✓ **EZ Align™** pump rail system for simple belt adjustments
- ✓ **Auto ON/Off** with time delay shutdown saves time & effort

#### Options...

185°F inlet temp rating option (-HT), Cat pump upgrade with 190°F inlet temp rating (-CAT), Wall mount brackets, sideways mount (ACW09), Wall mount hose reels (AR188), Wheel/handle kit (AHS15), Float tank/inlet soap injection option (WT0CW – not compatible with high temp options or 8gpm models), Multi station outlets (ACW20), Wall mount remote options (AEN35 or AEN22)



Shown with optional wheel / handle kit

TO: \_\_\_\_\_

COMMENTS: \_\_\_\_\_

YOUR PRICE: \_\_\_\_\_

DISTRIBUTED BY: \_\_\_\_\_